



ENGLISH

INSTALLATION & ELECTRICAL CONNECTION

INSTALLATION

1. Turn off power at main fuse box.
2. Fasten open end of ground wire attached to backplate (A) to ground screw of junction box.
3. Mount backplate (A) to junction box with 2 screws supplied. Make sure black and white wires of junction box run through the middle opening of the backplate.
4. Connect black and white wires of power supply to black and white wires of the fixture. **NOTE:** All wire connections should be made with wire nuts or marlets (included) and pushed back into junction box.
5. Mount finishing plate of bracket (B) over the 2 screws of backplate (A). Secure with 2 locknuts (C).

GLASS AND BULB INSTALLATION

1. Use G9 base bulbs (25Wmax).
2. Slip glass into end slots over bulb.

TURN ON POWER

ENJOY YOUR EasyLite™ LIGHTING PRODUCT

See Diagram (B) for Mounting Hardware Required



EasyLITE™



BR-2DAK-2N shown

THANK YOU

You've just purchased a lighting product designed and built to provide you with many years of enjoyment.

REED

Vous venez d'acheter un luminaire conçu pour vous donner des années de plaisir.

GRACIAS

¡Usted acaba de adquirir un excelente producto de alumbrado diseñado y construido para proveerle muchos años de satisfacción.

DAKOTA BATHBARS INSTRUCTIONS

- Please read all instructions prior to installation.
- We recommend a certified electrician for the installation of this fixture.
- Before installing fixture disconnect power by turning the circuit breaker or by removing the fuse at the fuse box.
- Veuillez lire les instructions avant de commencer l'installation.
- Consultez un électricien qualifié pour l'installation de ce produit.
- Coupez le courant au boîtier principal.
- Lea por favor todas las instrucciones antes de la instalación.
- Recomendamos a un electricista certificado para la instalación de este accesorio.
- Antes de instalar el accesorio, desconecte la energía apagando el interruptor o quitando el fusible en la caja principal.

EasyLITE™

www.easy-lite.com